

Datasheet



KM25

Graphic LCD keypads KM25

KM25 is a premium class LCD keypad that is suited for all SECOLINK alarm systems. It has integrated proximity tag reader that allows to use it as an access control module. Perfectly smooth, easy to clean surface with touch screen feature allows to project frequently used commands directly on screen. The control of the system became as easy as never before. Due to built-in radio transceiver, the keypad supports up to 16 wireless zones.



Features	KM25
Product type	Alarm system + access control module
On-Board zones	-
On-Board PGM	-
Ambient temperature measurement	-
Integrated proximity tag reader	Yes (on Stage 2)
Maximum cards (transponder/tag)	2000 (on Stage 2)
LCD type	Graphic: 240 x 120 dots, KM25 - mono LCD, KM25c - color LCD
Keys in keypad	25
Programmable fast keys (F-Keys)	32 (on Stage 2)
Data bus protocol	KRBUS, wireless KRBUS (on Stage 3)
Zone loop (detector) type	Wireless
Maximum wiring distance to CP	300 m
Power supply	9 - 14 V
Voltage measurement on keypad	Yes
Current consumption	Backlight on 110 mA, Backlight off < 50 mA, When alarming <220 mA
On-Board sounder	Speaker
Backlight color	Display = blue, keypad = blue
Character set	Major character sets of the world.
User interface type	Navigation menu with frequently used menu commands on touch screen.
Overall dimensions W x H in mm	92 x 134
Environmental compliance	ROHS
Operating temperature	0°C up to +50°C
Interface with PC (programming, firmware update)	USB mini-B

SECOLink

EASY TO INSTALL, EASY TO USE



ΗΛΚΑ Α.Ε.

ΙΔΙΩΤΙΚΗ ΕΠΙΧΕΙΡΗΣΗ ΠΑΡΟΧΗΣ ΥΠΗΡΕΣΙΩΝ ΑΣΦΑΛΕΙΑΣ
Αρ. Αδείας Λειτουργίας Υπ. Δημοσίας Τάξης 3015/39/60/97-μγ

Τεμπών 14, 153 42, Αγ. Παρασκευή Αττικής
Τηλ.: 210-6071510, Fax: 210-6071599

sales@ilka.gr

www.ilka.gr

www.ilka.gr/products

