

Datasheet



BK4

Magnetic door contact BK4

BK4 is wireless magnetic door contact with extra 3 inputs for external detectors. Magnetic contact and each input comes with unique ID for alarm transmission. BK4 can serve 4 detectors (zones) with 1 radio device.



Features	BK4
Description	Transmitter with 3 inputs and magnetic door contact
Compatible receivers	P16, P32, P64, EXT116s, EXT11, KM25
Operating frequency	868 MHz
Communication range in building	Up to 100m
Communication with hopping code	Selectable
2-way technology	Yes
Contact Open transmission	Yes
Contact Close transmission	Yes
Tamper transmission	Yes
Battery low status transmission	Yes
Supervision transmission	Selectable (every 1h for Grade 1, Custom; every 20 min for Grade 2)
In-built magnetic contact	Yes
In-built inputs for external detectors	3
External detector = magnetic contact	Yes
External detector = roller type detector	Yes
In-built output to power the external detector	-
Unique ID number for magnetic contact	Yes
Unique ID number for every in-built input	Yes
Power supply	Lithium battery, ½ AA, 3.6V
Battery life	>3 years
White color model	BK4
Brown color model	BK4_br
Overall dimensions W x H x L in mm	27 x 23.6 x 75
Operating humidity	0% - 70%
Operating temperature	-5°C up to +50°C

SECOLink

EASY TO INSTALL, EASY TO USE



ΗΛΚΑ Α.Ε.

ΙΔΙΩΤΙΚΗ ΕΠΙΧΕΙΡΗΣΗ ΠΑΡΟΧΗΣ ΥΠΗΡΕΣΙΩΝ ΑΣΦΑΛΕΙΑΣ
Αρ. Αδείας Λειτουργίας Υπ. Δημοσίας Τάξης 3015/39/60/97-μγ

Τεμπών 14, 153 42, Αγ. Παρασκευή Αττικής
Τηλ.: 210-6071510, Fax: 210-6071599

sales@ilka.gr

www.ilka.gr

www.ilka.gr/products

