

Datasheet



BT1

Temperature sensor BT1

BT1 is a long range, two way, wireless temperature sensor. Every hour temperature value could be transmitted to the control panel and displayed on the keypad or SECOLINK PRO application.



Features	BT1
Description	Temperature sensor
Compatible receivers	P16, P32, P64, EXT116s, KM25
Operating frequency	868 MHz and other (depends on national regulation)
Communication range in building	Up to 100m
Communication with hopping code	Selectable
2-way technology	Yes
Zone violation	-
Tamper transmission	Yes
Battery low status transmission	Yes
Temperature sensor	Yes
Motion detector (PIR)	-
Supervision transmission	Selectable (every 1h for Grade 1, Custom; every 20 min for Grade 2)
LED indicator	-
Pet immune	-
Lens coverage angle	-
Lens coverage distance	-
Unique ID number for motion detector (PIR)	-
Unique ID number for temperature sensor	Yes
Power supply	Lithium battery, ½ AA, 3.6V
Battery life	~3 years
Overall dimensions W x H x L in mm	27 x 23.6 x 75
Operating humidity	0% - 70%
Operating temperature	-5°C up to +55°C

SECOLink

EASY TO INSTALL, EASY TO USE



ΗΛΚΑ Α.Ε.

ΙΔΙΩΤΙΚΗ ΕΠΙΧΕΙΡΗΣΗ ΠΑΡΟΧΗΣ ΥΠΗΡΕΣΙΩΝ ΑΣΦΑΛΕΙΑΣ
Αρ. Αδείας Λειτουργίας Υπ. Δημοσίας Τάξης 3015/39/60/97-μυ

Τεμπών 14, 153 42, Αγ. Παρασκευή Αττικής
Τηλ.: 210-6071510, Fax: 210-6071599

sales@ilka.gr

www.ilka.gr

www.ilka.gr/products

