

# PS-4805-3A

## Features:

1. 144W Output Power Adapter
2. Output voltage & current: DC48V 3A
3. Input voltage range: 85~264VAC
4. Built in EMI filter with tiny ripple
5. 100% full load burn-in test
6. Air Cooling
7. Protection: Short circuit/ Overload/ Over voltage/ Over temperature



## Specification:

Model	PS-4805-3A	
Output	DC output Voltage	48V±10%
	Output Current Range	0-3A
	Wave and Noise	120mVp-p
	DC output Power	144W
	Efficiency	85%
	DC Voltage Adjustable Scope	(at full load) ≤0.5%
Input	Voltage Range	85~264VAC 47-63Hz
	Input Current	0.14A/115V, 0.07A/230V
	Leakage Current	<1mA/ 240VAC
	Inrush Current	Cold start 20A/120VAC, 40A/230VAC
Protection	Over-load	105%~135%, Protection type: Constant current limiting, recovers automatically after fault condition is removed
	Over-voltage	105%---150% Rated Voltage, Protection type: Shut off
	High-temperature	RTH3>=65°C FAN ON<=55°C FAN OFF>=80°C Cut off output(5~15V)
Environment	Working temperature and humidity	-10°C~+50°C, 20~90%RH
	Store temperature and humidity	-20°C~+85°C, 10~95%RH
	Temperature coefficient	±0.03%/°C(0~50°C)
	Vibration	10~500Hz,2G 10min./1cycle,Period for 60min,EACH AXES
Safety	Withstand voltage	I/P-O/P: 1.5KVAC, I/P-FG: 1.5KVAC, O/P-FG: 0.5KVAC

	Isolation resistance	I/P-O/P,I/P-FG,O/P-FG: 100M Ohms/500VDC
Standard	CE EMC Standard	EN55015:2013+A1:2015, EN61547:2009, EN61000-3-2:2014, EN61000-3-33:2013
	CE LVD Standard	EN61347-2-13:2014+A1:2017, EB61347-1:2015
	ROHS Standard	IEC 62321: 2013, EPA3050B:1996, EN1122:2001, EPA3052:1996, EPA3060A, etc.
Other	Dimension	70*39*31mm (L*W*H)
	Weight	0.058kg
	<p>1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.</p> <p>2. Ripple &amp; noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf &amp; 47uf parallel capacitor.</p> <p>3. Tolerance : includes set up tolerance, line regulation and load regulation.</p> <p>4. I/P-O/P: Input and output interval, I/P-FG: Input and enclosure, O/P-FG: Output and enclosure</p>	